



## CDM8240

IBundle Dispensing Module  
Maximum performance,  
minimal costs

### Description

The CDM8240 bundle dispensing module -the fruit of years of research and development- is a market leading cash dispensing module of which GRGBanking possesses full independent intellectual property rights. As a combination of advanced functionalities and a low cost of ownership, the CDM8240 offers superior performance and high reliability whilst it is easy to operate and maintain. All this and more makes the CDM8240 an ideal solution for ATMs and other self-service application.

## CDM8240

IBundle Dispensing Module  
Maximum performance, minimal costs

CDM8240 bundle dispensing module provides 4 advanced features of GRG's leading technology with all independent intellectual property rights owned by GRG.

### Reliable


- Opto-Electrical Detecting, delivers accurate detection even when notes are severely degraded.
- High security cassettes and a separate reject tray with lock and seal-leading.
- Unique log record and inquiry function, enables to record and check every transaction.
- Intelligent
- Unique self-calibrating function, automatically compensates for assembling errors.
- Offline diagnosis system enables convenient troubleshooting.

- Auto retract function
- Flexible
- Modular design, easy to assemble and disassemble
- Front or rear service access for convenient maintenance
- Optional long throat for the presenter
- High process speed and capacity
- Friction feed, able to handle various currencies
- Dispensing at a high speed of 7 notes/ second
- Maximum 3000 notes per cassette, expandable up to 4 cassettes, 12000 notes in total


### Specifications

- **Media ranges**  
Length: 110mm ~172 mm  
Width: 55mm ~85 mm  
Thickness: 0.06mm ~0.18 mm  
Dispensing system: Friction feed, Bundle dispensing, 7 notes/second  
Maximum notes per transaction: 60 notes  
Low level detection: 50~250 notes (adjustable)  
Reject mode: Single/Bundle  
Maintenance: Front/Rear
- **Note Cassette**  
Expandability: Up to 4 Cassette capacity: 3000 notes  
Reject tray capacity: 100 (single area) + 250(bundle area)  
Security: Mechanical lock and lead sealing
- **Weight**  
standard throat: 42 Kg long throat: 44 Kg (two cassettes weight, with the increase of every cassette, the weight shall be added by 11kg.)  
Communication interface: RS-232/ USB (optional)  
Operating environment: Temperature: 00C~500C Humidity: 20%~90% non-condensing
- **Power supply**  
Input voltage : 110V±10%; 220V±10% Consumption : Idle 30W; Operating 100W

### Dimensions



Front Service standard throat



Rear service, standard throat

The dimensions above are based on 2 cassettes height, with the increase of every cassette, the height shall be added by 142.5mm

Specifications are subject to update without prior notice. Please consult GRG Banking or its representative for the latest information.

### GRG Banking Equipment Co., Ltd

Add: 9 Kelin Road, Science City, Luogang District,  
Guangzhou, China 510663  
Tel: +86 20 82188379/82188564  
Fax: +86 20 82189024

Copyright by GRG Banking Equipment Co., Ltd.  
All rights reserved@201011MD01

[www.GRGBanking.com](http://www.GRGBanking.com)